

TECHNICAL DATA SHEET OF ELECTRICAL ROTARY TABLE (VARIABLE ROTATION)

ROTARY TABLE MODEL		CSTR 500	CSTR 550	CSTR 600	CSTR 650	CSTR 700	CSTR 750	CSTR 850	CSTR 1000	CSTR 1200	CSTR 1400
ROTRAY TABLE DIAMETER	mm	505	545	605	645	705	745	845	995	1190	1390
ROTARY TABLE THICKNESS	mm	105	105	105	120	120	120	120	130	140	160
ROTARY TABLE WEIGHT	Kg	400	440	490	540	580	650	750	1200	1500	2500
MAXIMUM MOLD WEIGHT	Kg	420	500	580	680	800	1000	1500	2000	3000	4500
COOLING SYSTEM CIRCUIT		2*	2*	2*	2*	3*	3*	3*	4*	4*	6*
ELECTRIC ENGINE		OMRON	OMRON	OMRON	OMRON	OMRON	OMRON	OMRON	OMRON	OMRON	OMRON
ROTATION CICLE MIN-MAX	s	1-2	1-2	1-2	1-2	1.5-2.5	1.5-2.5	1.5-2.5	3-3.5	3.5-4	4-4.5
DIAMETER OF THE EXTRACTION FIX	mm	Ø13**	Ø13**	Ø13**	Ø13**	Ø17**	Ø17**	Ø17**	Ø21**	Ø21**	Ø21**
MATERIAL SPECIFICATION		1.2312	1.2312	1.2312	1.2312	1.2312	1.2312	1.2312	1.2312	1.2312	1.2312
INJECTION PRESS TYPE (CLAMPING FORCE)	t	100	125	150	175	200	250	300	400	600	800
* = The number of cooling circuit system could change, according to the dimension of the central Extraction hole, on the movable part											
**=The dimensione of the extraction fix diameter could change, according to the dimension of the extractoin central hole present on the movable part											